



Specification Wording

Exposed Ceiling Tiles



- Grid to be 24mm wide T sections in [1200x600 / 600x600] modules.
- Ceiling tile finish colour to be either [White Noise, Miraka, Blue, Meadow, Waitoa, Black or client custom colour].
- Material is made from recycled composite packaging. Any off cuts or damage tiles should be separated and returned to saveBOARD for recycling into new products. saveBOARD products achieves a 0.99 sustainability factor under Greenstar rating tool.
- Panel installation to be as per manufacturer's instructions and AS/NZS 2785.
- saveBOARD Exposed Ceiling Tiles to be Fire Group 3 per BCA Specification C1.10 clause 4. Testing has been completed to AS/NZS 3837 by NATA certified laboratory.
- Product to meet or exceed Green Star Interiors V1.3 - 12.1.2B. Product has been tested by NATA certified laboratory to ASTM D5116-2017 and contains < 1% of the VOC rate of 0.004 mg/m2/hr (standard is 0.500 mg/m2/hr).
- Tile weight for ceiling grid design is 7.0 kg/m2 based on 10mm thickness.
- System as a whole is to have a minimum of 10 years warranty by the manufacturer. Proof of validity of manufacturer's warranty is to be provided to the superintendent before practical completion.
- Installation to be done by an approved ceiling and partition contractor.
- See www.saveboard.nz for further information.
- **Address:** 30 Sunshine Ave, Te Rapa, Hamilton 3200, New Zealand

